





## TECHNICAL SPECIFICATIONS 120 V

VOLTS		120 V
AMPS		12.5A
WATTS		1465 watts
HEATER	HIGH	1465 watts
	LOW	750 watts
ı	FLAME AND TRAY	14.2 watts
LAMPS	TOP LIGHT	1.5 watts
	TOTAL WATTS	15.7 watts
ROTOR M	OTOR	1 at 2.9 watts
HEIGHT,WIDTH,DEPTH		15 \frac{5}{8}" \times 32 \frac{3}{8}" \times 5 \frac{1}{2}"
GLASS V	IEWING OPENING	13 ½"×30 ½"
SURROU	ND SIZE	16 <sup>7</sup> / <sub>8</sub> "×34 ½"
SHIPPING	S SIZE(H,W,D)	19 <sup>3</sup> / <sub>4</sub> "×39 <sup>5</sup> / <sub>8</sub> "×9"
SHIPPING	G WEIGHT	57 Lbs
	UNIT	46.08 Lbs
	GLASS FRONT	Included
PLUG LO	CATION	Left Side
CORD LE	NGTH	76"
APPROX	. HEATING AREA	400 sq ft



SERIES	MODEL		REV.
SYMMETRY-3	SYM-34		1
SCALE 1"=1'-0"	DATE: 03.01.22	SHEET 1 OF 1	